

# **BLANK PAGE**



# Indian Standard

# SPECIFICATION FOR GRADING OF VISCOSE RAYON CUT STAPLE FIBRES (REGULAR)

(Second Reprint JANUARY 1984)

UDC 677.463:620.168



@ Copyright 1971

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

## Indian Standard

### SPECIFICATION FOR GRADING OF VISCOSE RAYON CUT STAPLE FIBRES (REGULAR)

Silk, Man-Made Fibre and Products Sectional Committee, TDC 10

Chairman

Representing

SHRI D. N. SHROFF

Silk & Art Silk Mills' Association Ltd, Bombay

Members

SHRI K. C. BHANDARI

The Sirsilk Ltd, Sirpur-Kaghaznagar

SHRI S. K. MANAKTALA ( Alternate )

SHRI S. K. BOSE

National Test House, Calcutta

DP E. D. DARUVALA

Government of Uttar Pradesh

SERI O. P. DHAWAN

The Silk & Rayon Textiles Export Promotion Council, Bombay

SHRI I. B. DUTT

SHRI P. N. MAITRA ( Alternate )

Office of the Textile Commissioner, Bombay

Da M. P. Khera

Directorate General of Technical Development

SHRI M. P. SINGH (Alternate)

The Travancore Rayons Ltd, Rayonpuram

SHRI T. KRISHNAMACHARI SHRI P. S. HARIHARAKRISHNAN ( Alternate )

Chemicals and Fibres of India Ltd. Bombay

Shri R. Kunjur SHRI S. L. RAHEJA ( Alternate )

South India Viscose Ltd, Coimbatore

S IRI C. R. LINGIAH SHRI A. MUTHUSWAMY ( Alternate )

Association of Man-Made Fibre Industry, Bombay

SHRI S. P. MANDELIA SHRI R. C. MATHUR

Ministry of Defence (DGI)

SHRI R. R. KATIYAR ( Alternate )

OR C. N. K. MURTHY

Ministry of Defence (R & D)

SHRI P. S. NADKARNI ( Alternate ) SHRI I. H. PAREKH

The Gwalior Rayon Silk Mfg (Wvg) Co Ltd, Nagda

SHRI A. S. MEHTA ( Alternate ) DR M. D. PAREKH

The National Rayon Corporation Ltd, Bombay The Silk & Art Silk Mills' Research Association,

HRI J. G. PARIKH

Bombay Silk & Art Silk Mills' Association Ltd, Bombay Textiles Committee, Bombay

SHRI N. M. PATEL HRI A. S. RAMA RAO SHRI G. RANGANATH ( Alternate )

The National Rayon Corporation Ltd, Bombay

Dr S. I. TARAPOREWALA SHRI S. S. VAIDYA

The Millowners' Association, Bombay

SHRI S. M. CHARRABORTY,

Director General, ISI (Ex-officio Member)

Director (Tex)

Secretary

SHRI P. VENKATARAMAN Deputy Director (Tex), ISI

(Continued on page 2)

INDIAN STANDARDS INSTITUTION

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002

(Continued from page 1)

Man-Made Fibres and Yarns Subcommittee, TDC 10:1

Representing

DR M. D. PAREKE

The National Rayon Corporation Ltd, Bombay

Members

SERI ASHOK RAMANLAL SHRIK, C. BHANDARI

New Vinod Silk Mills Pvt Ltd, Bombay The Sirsilk Ltd, Sirpur-Kaghaznagar

SHRIS. K. MANAKTALA ( Alternate )

SHRI S. K. BOSE SHRI S. P. MULLICK ( Alternate )

National Test House, Calcutta

Chemicals and Fibres of India Ltd. Bombay SHRI B. R. DOLE

SHRI Y. G. DESHPANDE ( Alternate ) Shri R. Ethirajulu

The Indian Cotton Mills Federation, Bombay

Century Rayons, Bombay

SHRI P. M. JHAVERI

DR B. H. CHALISHAZAR ( Alternate ) DR V. G. KAMATH

Nirlon Synthetic Fibres & Chemicals Ltd. Bombay

SHRI B. DAS GUPTA ( Alternate ) DR M. P. KHERA

Directorate General of Technical Development

SHRI M. P. SINGH ( Alternate )

SHRI R. S. KIMATRAI SHRI VASHDEV P. DULANI ( Alternate )

Nanikram Sobhraj Mills Private Ltd. Ahmedabad The Travancore Rayons Ltd, Rayonpuram

SHRI T. KRISHNAMACHARI

SHRIP. S. HARIHARAKRISHNAN ( Alternate )

SHRI P. N. MAITRA

Office of the Textile Commissioner, Bombay South India Viscose Ltd, Coimbatore

SHRI A. MUTHUSWAMY DR C. ROSSI ( Alternate )

The Gwalior Rayon Silk Mfg (Wvg) Co Ltd, Nagda

SHRI I. H. PAREKH SHRI A. S. MERTA (Alternate)

The Silk & Art Silk Mills' Research Association,

SHRI J. G. PARIKH

Bombay Directorate General of Supplies & Disposals, New Delhi

SHRI I. L. PATEL

Silk & Art Silk Mills' Association Ltd, Bombay

SHRI V. B. HAJELA ( Alternate ) SHRI N. M. PATEL SHRI V. P. PATEL SHRI V. K. SHAH SHRI P. B. CHINOY (Alternate) DR S. I. TARAPOREWALA

Silk & Art Silk Mills' Association Ltd, Bombay Baroda Rayon Corporation Ltd, Baroda

SHRI V. R. TIBREWALA SHRI B. N. PATEL ( Alternate ) The National Rayon Corporation Ltd, Bombay Century Enka Ltd, Bombay

SHRI I. K. TURAKHIA

The Rayon Mills Commercial Corporation Ltd. Bombay

Ad hoc Study Group for Rayon Staple Fibre, TDC 10: 1/SG

· Convener

SHRI A. S. METHA

Gwalior Rayon Silk Mfg (Wvg) Co Ltd, Nagda

The Indian Cotton Mills Federation, Bombay

Members

PROF E. H. DARUWALLA SHRI R. N. RAO ( Alternate ) SHRI A. MUTHUSWAMY

South India Viscose Ltd, Coimbatore

The Silk & Art Silk Mills Research Association. SMT A. KAPLASH Bombay

# Indian Standard

### SPECIFICATION FOR GRADING OF VISCOSE RAYON CUT STAPLE FIBRES (REGULAR)

#### O. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 16 November 1970, after the draft finalized by the Silk, Man-Made Fibre and Products Sectional Committee had been approved by the Textile Division Council.
- 0.2 With the increase in the use of viscose rayon cut staple fibres in the different sectors of the textile industry, the demand for appropriate grade of fibre has arisen. This standard has, therefore, been prepared with the intention of clearly defining the various grades of viscose rayon cut staple fibres. It is hoped that this standard would enable the buyer to select the correct grade of fibre to suit his end requirement.
- 0.3 This standard is based on trade practices commonly followed in the country in this field.
- 0.4 Considerable assistance has been rendered by the Gwalior Rayon Silk Manufacturing (Weaving) Co Ltd, Nagda and South India Viscose Limited, Mettupalayam, in the preparation of this standard.
- 0.5 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS:2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE

1.1 This standard prescribes a method for grading of viscose rayon cut staple fibres (regular).

<sup>\*</sup>Rules for rounding off numerical values (revised).

#### 2. REQUIREMENTS — CHARACTERISTICS TO BE TESTED

- 2.1 The material shall be tested in respect of the following characteristics:
  - a) Fibre length,
  - b) Denier, and
  - c) Dry strength.
- 2.1.1 The fibre shall be identified by the method prescribed in IS: 667-1955\*.

#### 3. SAMPLING

3.1 Representative material for testing the requirements shall be sampled according to 3 of IS: 4807-1968†.

#### 4. ATMOSPHERIC CONDITIONS FOR TESTING

4.1 All the tests shall be carried out in a standard atmosphere of  $65 \pm 2$  percent relative humidity and  $27 \pm 2^{\circ}$ C (see also IS: 196-1966‡).

#### 5. CONDITIONING OF TEST SAMPLE

- 5.1 Prior to test, the fibres shall be conditioned to moisture equilibrium in a standard atmosphere of  $27 \pm 2^{\circ}$ C temperature and  $65 \pm 2$  percent RH.
- 5.2 When the fibres have been left in such an atmosphere for at least 24 hours in such a way as to expose as far as possible all portions of the fibres to the atmosphere, they shall be deemed to have reached moisture equilibrium.

#### 6. TEST METHODS

- 6.1 Fibre Length Fibre length characteristics, such as mean length and effective length, shall be evaluated according to 6.2 of IS: 4807-1968†.
- 6.1.1 Evaluation of Proportion of Overlong Fibres From the effective length obtained as in 6.1, add 5 mm if the declared staple length of the consignment is below 50 mm and 10 mm if the declared staple length of the consignment is above 50 mm to the effective length. Collect such fibres (from the oiled glass sheet) which are longer than the sum total of this length and weigh them. From this weight, calculate the percentage of overlong fibres in the consignment. Repeat the test once again and take the average of the two values as the percentage of overlong fibres.

<sup>\*</sup>Simple methods for identification of common commercial textile fibres.

<sup>†</sup>Methods of testing viscose rayon staple fibres.

<sup>‡</sup>Atmospheric conditions for testing (revised).

6.1.2 Fibre Length Deviation — Calculate the fibre length deviation by the following formula:

$$F = \frac{100 (A - B)}{B}$$

where

F = fibre length deviation,

A =effective length, and

B = declared staple length of the consignment.

- **6.2 Denier** Calculate the denier of the fibres by following the method given in **6.3** of IS:4807-1968\*.
- 6.2.1 Deviation in Denier Calculate the percentage deviation in denier by the following formula:

$$D = \frac{100 \; (A-B)}{B}$$

where

D = deviation in denier,

A = denier of conditioned fibre, and

B =declared denier of the consignment.

6.3 Strength—The dry strength of the fibres shall be determined according to 6.4 of IS:4807-1968\*.

#### 7. GRADING

7.1 The material shall be graded into any one of the three grades depending upon the number of points obtained. For grading the material into Grade 1, the material shall receive more than 400 points. For grading the material into Grade 2, the material shall receive points from 300 to 400. For grading the material into Grade 3, the material shall receive points less than 300.

### 8. METHOD FOR AWARDING POINTS

8.1 The material shall be awarded points for the individual characteristics based on the details given in Table 1.

### 9. BASIS FOR ALLOCATION OF POINTS

9.1 Fibre length being the most important characteristic among all the characteristics from the point of view of spinning, it has been allotted the maximum number of points. Other characteristics have been allotted points in the order of their importance.

<sup>\*</sup>Methods of testing viscose rayon staple fibres.

### TABLE 1 METHOD OF AWARDING POINTS

( Clause 8.1 )

	CHARACTERISTIC	Points	POINTS	Points	Points
	(1)	(2)	(3)	(4)	(5)
Α.	When the Declared Denier is Below 2:				
	Extra long fibre, percent	150 if 6:0 or below	120 if between 8.0 and 6.0	90 if between 12:0 and 8:0	60 if beyond 12
	Fibre length (effec- tive) deviation, percent	150 if ± 6·0 and below	120 if between ±8.0 and ±6.0	90 if between $\pm 10.0$ and $\pm 8.0$	60 if beyond ±10.0
	Denier deviation, percent	100 if up to and including ±10.0	80 if between ±12.0 and ±10.0	60 if between ±14.0 and ±12.0	40 if beyond ±14·0
•	Dry strength on single fibre tester (g/d	100 if above 2·3	80 if between 2.15 and 2.3 (including)	60 if between 1.9 and 2.15 (including)	40 if below 1.9
В.	When the Declared Denier is Above 2:				
	Extra long fibre, percent	150 if 6·0 or below	120 if between 8:0 and 6:0	90 if between 12:0 and 8:0	60 if beyond 12.0
	Fibre length ( effec- tive ) deviation, percent	150 if ± 6·0 and below	120 if between ±8.0 and ±6.0	90 if between $\pm 10.0$ and $\pm 8.0$	60 if beyond ±10.0
	Denier deviation, percent	100 if up to and including ± 10	80 if between $\pm$ 12 and $\pm$ 10	60 if between $\pm$ 14 and $\pm$ 12	40 if beyond ± 14
	Dry strength on single fibre tester (g/d)	100 if above 2.0	80 if between 1.8 and 2.0	60 if between 1.6 and 1.8	40 if below 1·6

### INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

Base Units			
Quantity	Unit	Symbol	
Length	metre	m	
Mass	killogram	kg	
Time	second		
Electric current	ampere	. A	
Thermodynamic temperature	kelvin	K	
Luminous Intensity	candela	cd	
Amount of substance	mole	mol	
Supplementary Units			
Quantity	Unit	Symbol	
Plane angle	radian	rad	
Solid angle	steradian	31	
Derived Units			
Quantity	Unit	Symbol	Conversion
Force	newton	N	1 N - 1 kg. 1 m/a2
Energy	Joule	3	1 J = 1 N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb - 1 V.s
Flux density	teste	T	1 T = 1 Wb/m2

Hz

S

Pa.

1 Hz = 1 c/s (s-1)

1 S = 1 A/V 1 Pa = 1 N/m<sup>3</sup>

hertz

siemens

pascal

#### INDIAN STANDARDS INSTITUTION

Frequency

Electric conductance

Pressure, stress

EW DELHI 110002 Telegrams : Manai	ksan	isti	ha
7	elep	ho	D8
BOMBAY 400007	37 5	97	29
CALCUTTA 700072	23-0	80	02
MADRAS 600020	41.1	24.	42
AHMADABAD 380001	2 (	13	91
BANGALORE 560002	2 7	76	49
BHOPAL 462003	81	27	10
BHUBANESHWAR 751014	5 1	36	27
CHANDIGARH 160017	21	13	20
HYDERABAD 500001	22 1	10	83
JAIPUR 302006	6.1	18	32
KANPUR 208005	B 1	2	72
PATNA 800013	6.2	28	80
TRIVANDRUM 895001	- 3	12	27
	Telegrams: Manai T BOMBAY 400007 CALCUTTA 700072 MADRAS 600020 AHMADABAD 380001 BANGALORE 360002 BHOPAL 462003 BHUBANESHWAR 751014 CHANDIGARH 160017 HYDERABAD 500001 JAIPUR 302006 KANPUR 208005 PATNA 800013	Telegrams : Manaksan Sombay 400007 37 : CALCUTTA 700072 23-4 MADRAS 600020 41 :  AHMADABAD 380001 2 : BANGALORE 560002 2 : BHOPAL 462003 6 : BHUBANESHWAR 751014 5 : CHANDIGARH 160017 2 : HYDERABAD 500001 22 : JAIPUR 302006 6 : KANPUR 208005 8 : PATNA 800013 6 :	Telegrams : Manaksansti Telepho BOMBAY 400007 37 97 CALCUTTA 700072 23-08 MADRAS 600020 41 24  AHMADABAD 380001 2 03 BANGALORE 560002 2 76 BHOPAL 462003 6 27 BHUBANESHWAR 751014 5 36 CHANDIGARH 160017 2 83 HYDERABAD 500001 22 10 JAIPUR 302006 6 98 KANPUR 208005 B 12 PATNA 800013 6 28